

Safety Data Sheet

[®] Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	0257S1NL	Revision Date:	12/05/2022	
	Product Name:	CARBOCRYLIC 3350	Supercedes Date:	02/21/2022	
1.2	Relevant identified uses of the substance or mixture and uses advised against	Monocomponent industrial coating - Industrial use.			
1.3	B Details of the supplier of the safety data sheet				
	Manufacturer:Carboline Global Inc.2150 Schuetz RoadSt. Louis, MO USA 63146				
		Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645			
	Datasheet Produced by:	Schlereth, Ken - regulatory@carboline.com			
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-68	1-6669		

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3

2.2 Label elements

Symbol(s) of Product

None

Signal Word

Named Chemicals on Label None

HAZARD STATEMENTS

Hazardous to the aquatic environment, Chronic, category 3 PRECAUTION PHRASES	H412	Harmful to aquatic life with long lasting effects.
	P273	Avoid release to the environment.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients				
Name According to EEC TITANIUM DIOXIDE	<u>EINEC No.</u> 236-675-5	<u>CAS-No.</u> 13463-67-7	<u>%</u> 10 - <25	Classifications
HEXYLENE GLYCOL	203-489-0	107-41-5	1.0 - <2.5	H315-319
POLYETHYLENE GLYCOL		25322-68-3	1.0 - <2.5	H319
CARBON BLACK	215-609-9	1333-86-4	1.0 - <2.5	
DIURON	206-354-4	330-54-1	0.1 - <1.0	H302-351-373-400-410

CAS-No.	M-Factors
13463-67-7	0
107-41-5	0
25322-68-3	0
1333-86-4	0
330-54-1	10
Remarks:	CAS No 13463-67-7: Note 10

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Evacuate personnel to safe areas. The product is not flammable. Use NIOSH approved respiratory protection.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Avoid breathing vapors, mist or gas. Wash thoroughly after handling. **PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks. Do not freeze. **STORAGE CONDITIONS:** Do not freeze. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	N/E
HEXYLENE GLYCOL	107-41-5	25 PPM	50 PPM	25 PPM
POLYETHYLENE GLYCOL	25322-68-3	N/E	N/E	N/E
CARBON BLACK	1333-86-4	3 MGM3	N/E	N/E
DIURON	330-54-1	10 MGM3	N/E	N/E
Name	CAS-No.	<u>OSHA PE</u>	L <u>OSHA ST</u>	EL
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E	
HEXYLENE GLYCOL	107-41-5	N/E	N/E	
POLYETHYLENE GLYCOL	25322-68-3	N/E	N/E	
CARBON BLACK	1333-86-4	3.5 MGM3	N/E	
DIURON	330-54-1	10 MG/M3	N/E	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Viscous Liquid, Various Colors
	Physical State	Liquid
	Odor	Ammoniacal
	Odor threshold	N/D

	рН	N/D
	Melting point / freezing point (°C)	32F (0C)
	Boiling point/range (°C)	176 F (80 C) - 446 F (230 C)
	Flash Point (°C)	301F (149C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	0.6 - 24.6
	Vapour Pressure, mmHg	N/D
	Vapour density	Heavier than Air
	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
2	Other information	
	VOC Content g/I:	250
	Specific Gravity (g/cm3)	1.27

10. Stability and Reactivity

10.1 Reactivity

9.2

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid Heat, flames and sparks. Do not freeze.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1	Information on toxicological effe	ects
	Acute Toxicity:	
	Oral LD50:	N/D
	Inhalation LC50:	N/D
	Irritation:	Unknown
	Corrosivity:	Unknown
	Sensitization:	Unknown
	Repeated dose toxicity:	Unknown
	Carcinogenicity:	Unknown
	Mutagenicity:	Unknown
	Toxicity for reproduction:	Unknown
	STOT-single exposure:	Unknown
	STOT-repeated exposure:	Unknown
	Aspiration hazard:	Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	<u>Gas LC50</u>	<u>Dust/Mist</u> LC50
TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information
HEXYLENE GLYCOL	>2000 mg/kg, oral, rat		Not Available	0.000	0.000
POLYETHYLENE GLYCOL	Not Available		Not Available	0.000	0.000
CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available		
DIURON	1017 mg/kg, oral, rat		Not Available	0.000	0.000
	TITANIUM DIOXIDE HEXYLENE GLYCOL POLYETHYLENE GLYCOL CARBON BLACK	TITANIUM DIOXIDE25000 mg/kg, oral (rat)HEXYLENE GLYCOL>2000 mg/kg, oral, ratPOLYETHYLENE GLYCOLNot AvailableCARBON BLACK8000 mg/kg oral, ratDIUBON1017 mg/kg,	TITANIUM DIOXIDE25000 mg/kg, oral (rat)Not AvailableHEXYLENE GLYCOL>2000 mg/kg, oral, ratNot AvailablePOLYETHYLENE GLYCOLNot AvailableNot AvailableCARBON BLACK8000 mg/kg oral, ratNot AvailableDIUBON1017 mg/kg,Not Available	TITANIUM DIOXIDE25000 mg/kg, oral (rat)Not AvailableNot AvailableHEXYLENE GLYCOL>2000 mg/kg, oral, ratNot AvailableNot AvailablePOLYETHYLENE GLYCOLNot AvailableNot AvailableNot AvailableCARBON BLACK8000 mg/kg oral, ratNot AvailableNot AvailableDIURON1017 mg/kg,Not AvailableNot Available	TITANIUM DIOXIDE25000 mg/kg, oral (rat)Not AvailableNot AvailableNo InformationHEXYLENE GLYCOL>2000 mg/kg, oral, ratNot Available0.000POLYETHYLENE GLYCOLNot AvailableNot Available0.000CARBON BLACK8000 mg/kg

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

 EC50 48hr (Daphnia):
 Uni

 IC50 72hr (Algae):
 Uni

 LC50 96hr (fish):
 Uni

Unknown Unknown Unknown Date Printed: 04/21/2023

12.2 Persistence and degradability:	Unknown				
12.3 Bioaccumulative potential:	Unknown	Unknown			
12.4 Mobility in soil:	Unknown				
12.5 Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.				
12.6 Other adverse effects:	Unknown				
CAS-No. Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>		
13463-67-7 TITANIUM DIOXIDE	No information	No information	No information		
107-41-5 HEXYLENE GLYCOL	No information	No information	No information		
25322-68-3 POLYETHYLENE GLYCOL	No information	No information	No information		
1333-86-4 CARBON BLACK	No information	No information	No information		
330-54-1 DIURON	1.4 mg/l (Daphnia magna)	0.022 mg/l (Alga)	5.6 mg/l (Rainbow Trout)		

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	Transport Information	
14.1	UN number	None
14.2	UN proper shipping name	Not Regulated
	Technical name	N/A
14.3	Transport hazard class(es)	None
	Subsidiary shipping hazard	N/A
14.4	Packing group	N/A
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	N/A
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	<u>%</u>
DIURON	330-54-1	0.14

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	<u>CAS-No.</u>
WATER	7732-18-5
ACRYLIC EMULSION	PROPRIETARY
ALUMINUM SILICATE	1332-58-7
PROPYLENE GLYCOL	57-55-6
enneulyania Diaht Ta Know	

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
WATER	7732-18-5
ACRYLIC EMULSION	PROPRIETARY
ALUMINUM SILICATE	1332-58-7
PROPYLENE GLYCOL	57-55-6
YELLOW IRON OXIDE	51274-00-1

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed. H315 Causes skin irritation.

H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Date Printed: 04/21/2023