

Safety Data Sheet

[®] Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	0479B1NL	Revision Date:	12/05/2022
	Product Name:	CARBOZINC 85 PART B	Supercedes Date:	05/28/2015
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.		
1.3	Details of the supplier of the safety	data sheet		
	Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146		
		Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
	Datasheet Produced by:	Schlereth, Ken - regulatory@carboline.c	om	
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US CHEMTREC +1 703 5273887 (Outside L HEALTH - Pittsburgh Poison Control 1-4	(SÌ	

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Acute, category 1 Hazardous to the aquatic environment, Chronic, category 1 Eye Irritation, category 2 Flammable Liquid, category 3 Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

BISPHENOL A EPOXY RESIN

HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Irritation, category 2	H226 H315	Flammable liquid and vapour. Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, Acute, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, Chronic, category 1	H410	Very toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P391	Collect spillage.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.
ADDITIONAL INFORMATION		
	Note_P 64742-95-6	Note P : The classification as a carcinogen or mutagen need not apply; the substance, CAS 64742-95-6, contains less than 0,1 % w/w benzene

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. C	3. Composition/Information On Ingredients						
3.2	Mixtures						
Hazar	dous ingredients						
Name	According to EEC	EINEC No.	CAS-No.	<u>%</u>	<u>Classifications</u>		

Date Printed: 12/21/2022

Product: 0479B1NL

ZINC (DUST OR FUME)	231-175-3	7440-66-6	75 - 100	H250-400-410	Aquatic Acute 1, Aquatic Chronic 1, Pyr. Sol. 1
BISPHENOL A EPOXY RESIN	500-033-5	25068-38-6	2.5 - <10	H315-317-319-411	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1
AROMATIC HYDROCARBON	265-199-0	64742-95-6	2.5 - <10	H304-315-319-332-335-336-351 -411	Acute Tox. 4 Inhalation, Aquatic Chronic 2, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI
ZINC OXIDE	215-222-5	1314-13-2	1.0 - <2.5	H400-410	Aquatic Acute 1, Aquatic Chronic 1
N-BUTYL ACETATE	204-658-1	123-86-4	1.0 - <2.5	H226-336	Flam. Liq. 3, STOT SE 3 NE
SOLVENT NAPHTHA	265-149-8	64742-47-8	1.0 - <2.5	H304-315-335-336	Asp. Tox. 1, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI

CAS-No.	M-Factors
7440-66-6	0
25068-38-6	0
64742-95-6	0
1314-13-2	0
123-86-4	0
64742-47-8	0
Remarks:	CAS No. 25068-38-6 identified as CAS No. 1675-54-3, EC No. 216-823-5 under REACH Registration

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible LiquidProvide adequate ventilation. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Combustible material. Cool containers / tanks with water spray.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. **PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
ZINC (DUST OR FUME)	7440-66-6	N/E	N/E	N/E
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E	N/E
AROMATIC HYDROCARBON	64742-95-6	300.0 PPM	N/E	N/E
ZINC OXIDE	1314-13-2	2 MGM3	10 MGM3	N/E
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
SOLVENT NAPHTHA	64742-47-8	100.0 PPM	N/E	N/E

Name	CAS-No.	OSHA PEL	OSHA STEL
ZINC (DUST OR FUME)	7440-66-6	5.0 MG/M3	N/E
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E
AROMATIC HYDROCARBON	64742-95-6	500.0 PPM	N/E
ZINC OXIDE	1314-13-2	5 MGM3 5 MGM3 15 MGM3	N/E
N-BUTYL ACETATE	123-86-4	710 MGM3, 150 PP 9 5	60 MGM3, 200 PPM
SOLVENT NAPHTHA	64742-47-8	500.0 PPM	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Viscous Grey Liquid
	Physical State	Liquid
	Odor	Ероху
	Odor threshold	N/D
	рН	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	176 F (80 C) - 500 F (260 C)
	Flash Point (°C)	110F (43C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	0.6 - 7.6
	Vapour Pressure, mmHg	N/D
	Vapour density	Heavier than Air

	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/I:	300
	Specific Gravity (g/cm3)	3.48

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

- **10.2 Chemical stability** Stable under normal conditions.
- **10.3 Possibility of hazardous reactions** Hazardous polymerisation does not occur.
- 10.4 Conditions to avoid

Heat, flames and sparks.

- **10.5 Incompatible materials** Strong oxidizing agents.
- 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1	Information on toxicological eff	ects
	Acute Toxicity:	
	Oral LD50:	N/D
	Inhalation LC50:	N/D
	Irritation:	Unknown
	Corrosivity:	Unknown
	Sensitization:	Unknown
	Repeated dose toxicity:	Unknown
	Carcinogenicity:	Unknown
	Mutagenicity:	Unknown
	Toxicity for reproduction:	Unknown
	STOT-single exposure:	No Information
	STOT-repeated exposure:	No Information
	Aspiration hazard:	No Information

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	<u>Gas LC50</u>	<u>Dust/Mist</u> LC50
7440-66-6	ZINC (DUST OR FUME)	>2000 mg/kg, oral, rat	Not Available	Not Available	0.000	>5.4 mg/L, / 4Hr ,rat, inh
25068-38-6	BISPHENOL A EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	>20 mL/kg skin, sensitizer		
64742-95-6	AROMATIC HYDROCARBON	4700 mg/kg, oral, rat	Not Available	3670 ppm/8 hours, rat, inhalation	0.000	0.000
1314-13-2	ZINC OXIDE	15000 mg/kg, oral, rat	Not Available	Not Available	0.000	0.000
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat		
64742-47-8	SOLVENT NAPHTHA	Not Available	Not Available	Not Available	0.000	0.000

Additional Information:

No Information

12. Eco	ological Information			
12.1 Tox	icity:			
E	C50 48hr (Daphnia):	Unknown		
IC	C50 72hr (Algae):	Unknown		
L	C50 96hr (fish):	Unknown		
12.2 Pers	sistence and degradability:	Unknown		
12.3 Bioa	accumulative potential:	Unknown		
12.4 Mot	pility in soil:	Unknown		
	ults of PBT and vPvB essment:	The product does not meet	t the criteria for PBT/VPv	B in accordance with Annex XII
12.6 Oth	er adverse effects:	Unknown		
CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
7440-66-6	ZINC (DUST OR FUME)	No information	No information	No information
25068-38-6	BISPHENOL A EPOXY RESIN	2.1 mg/l (daphnia)	11 mg/l (algae)	1.3 mg/l (fish)
64742-95-6	6 AROMATIC HYDROCARBON	No information	No information	No information
1314-13-2	ZINC OXIDE	No information	No information	No information
123-86-4	N-BUTYL ACETATE	44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
64742-47-8	3 SOLVENT NAPHTHA	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.2 U	JN number JN proper shipping name rechnical name	UN 1263 Paint
Т	echnical name	
		N/A
14.3 T	ransport hazard class(es)	3
S	Subsidiary shipping hazard	N/A
14.4 P	Packing group	III
14.5 E	nvironmental hazards	Unknown
14.6 S	special precautions for user	Unknown
E	mS-No.:	F-E, S-E
	ransport in bulk according to Annex II f MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	<u>%</u>
ZINC (DUST OR FUME)	7440-66-6	79.66
ZINC OXIDE	1314-13-2	2.47

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

CAS-No.

CAS-No.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H250	Catches fire spontaneously if exposed to air.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.