

Safety Data Sheet

[®] Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	0952A1NL	Revision Date:	12/05/2022	
	Product Name:	CARBOGUARD 571 PART A	Supercedes Date:	05/04/2017	
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.			
1.3	Details of the supplier of the safety	data sheet			
	Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Information: Contact Carboline Technical Services at			
		1-800-848-4645			
	Datasheet Produced by:	Schlereth, Ken - regulatory@carboline.c	om		
1.4	Emergency telephone number:	elephone number: CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669			

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

EPOXY PHENOL NOVOLAC RESIN

HAZARD STATEMENTS

Skin Irritation, category 2 Skin Sensitizer, category 1 Hazardous to the aquatic environment, Chronic, category 2 PRECAUTION PHRASES	H315 H317 H411	Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.
	P261 P273 P280 P302+352 P333+313 P391	Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/ face protection. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

Mixtures 3.2

Name According to EEC	EINEC No.	CAS-No.	<u>%</u>	Classifications	
EPOXY PHENOL NOVOLAC RESIN	701-263-0	9003-36-5	75 - 100	H315-317-411	Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1
DIPHYNL ESTER	214-987-2	1241-94-7	2.5 - <10		

CAS-No.	M-Factors
9003-36-5	0
1241-94-7	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

Product: 0952A1NL

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Vapors may spread long distances and ignite.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Avoid breathing vapors, mist or gas. Wash thoroughly after handling. **PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash

hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	<u>ACGIH TWA</u>	ACGIH STEL	ACGIH Ceiling
EPOXY PHENOL NOVOLAC RESIN	9003-36-5	N/E	N/E	N/E
DIPHYNL ESTER	1241-94-7	N/E	N/E	N/E
Name	CAS-No.	<u>OSHA PEI</u>	<u>OSHA ST</u>	EL
EPOXY PHENOL NOVOLAC RESIN	9003-36-5	N/E	N/E	
DIPHYNL ESTER	1241-94-7	N/E	N/E	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Use only in an area equipped with explosion proof exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Viscous Liquid
	Physical State	Liquid
	Odor	Slight Phenolic
	Odor threshold	N/D
	pH	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	

		N/D - N/D
	Flash Point (°C)	206F (96C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	0.9 - 7.5
	Vapour Pressure, mmHg	N/D
	Vapour density	Heavier than Air
	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
2	Other information	
	VOC Content g/I:	6
	Specific Gravity (g/cm3)	1.19

10. Stability and Reactivity

10.1 Reactivity

9.2

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

- **10.5 Incompatible materials** Strong oxidizing agents.
- **10.6 Hazardous decomposition products** Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

		///
11.1	Information on toxicological eff	ects
	Acute Toxicity:	
	Oral LD50:	N/D
	Inhalation LC50:	N/D
	Irritation:	Unknown
	Corrosivity:	Unknown
	Sensitization:	Unknown
	Repeated dose toxicity:	Unknown
	Carcinogenicity:	Unknown
	Mutagenicity:	Unknown
	Toxicity for reproduction:	Unknown
	STOT-single exposure:	No Information
	STOT-repeated exposure:	No Information
	Aspiration hazard:	No Information

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	<u>Gas LC50</u>	<u>Dust/Mist</u> LC50
9003-36-5	EPOXY PHENOL NOVOLAC RESIN	>5000 mg/kg, oral, rat		Not Available	0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1	Toxicity:	
	EC50 48hr (Daphnia):	Unknown
	IC50 72hr (Algae):	Unknown
	LC50 96hr (fish):	Unknown
12.2	Persistence and degradability:	Unknown
12.3	Bioaccumulative potential:	Unknown
12.4	Mobility in soil:	Unknown
12.5	Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects:

Unknown

CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
9003-36-5	EPOXY PHENOL NOVOLAC RESIN	1.6 mg/l (Daphnia Magna)	1.8 mg/l (Green Algae)	0.55 mg/l (Rainbow Trout)
1241-94-7	DIPHYNL ESTER	No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	Transport Information	
14.1	UN number	UN3082
14.2	UN proper shipping name	Environmentally Hazardous Substance, Liquid, N.O.S.
	Technical name	(Epoxy Resin)
14.3	Transport hazard class(es)	9
	Subsidiary shipping hazard	N/a
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant: Yes (Epoxy Resin)
14.6	Special precautions for user	Unknown
	EmS-No.:	F-A, S-F
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CAS-No.

No TSCA 12(b) components exist in this product.

<u>%</u>

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
HYDROPHOBIC SILICA	67762-90-7
ADDITIVE	TRADE SECRET
Pennsylvania Right-To-Know	

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product. CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other	Information
-----------	-------------

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Date Printed: 12/21/2022