

# Safety Data Sheet

# Prepared in Accordance with HCS 29 C.F.R. 1910.1200

## 1. Identification of the Substance/Mixture and the Company/Undertaking

Product Identifier 121PA1NL 12/05/2022 **Revision Date:** Supercedes Date:

11/29/2017

PLASITE 4301 HT **Product Name:** 

PART A

Relevant identified uses of the

substance or mixture and uses

advised against

Component of

multicomponent industrial coatings - Industrial use.

Details of the supplier of the safety data sheet 1.3

> Carboline Global Inc. Manufacturer:

2150 Schuetz Road St. Louis, MO USA 63146

Regulatory / Technical Information: Contact Carboline Technical Services at

1-800-848-4645

Schlereth, Ken - regulatory@carboline.com **Datasheet Produced by:** 

CHEMTREC 1-800-424-9300 (Inside US) 1.4 Emergency telephone number:

CHEMTREC +1 703 5273887 (Outside US)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

## 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A Eye Irritation, category 2 Flammable Liquid, category 3 Reproductive Toxicity, category 2 STOT, repeated exposure, category 1 Skin Irritation, category 2

### 2.2 Label elements

## Symbol(s) of Product



## Signal Word

Danger

## Named Chemicals on Label

METHACRYLIC ACID, STYRENE, MICROCRYSTALLINE SILICA

## **HAZARD STATEMENTS**

| Flammable Liquid, category 3           | H226    | Flammable liquid and vapour.                                    |
|--|---------|---|
| Skin Irritation, category 2            | H315    | Causes skin irritation.   |
| Eye Irritation, category 2             | H319    | Causes serious eye irritation.                                  |
| Acute Toxicity, Inhalation, category 4 | H332    | Harmful if inhaled.   |
| Carcinogenicity, category 1A           | H350-1A | May cause cancer.   |
| Reproductive Toxicity, category 2      | H361d   | Suspected of damaging the unborn child.                         |
| STOT, repeated exposure, category 1    | H372    | Causes damage to organs through prolonged or repeated exposure. |
|  |         |   |

## **PRECAUTION PHRASES**

| P201         | Obtain special instructions before use.   |
|--------------|---|
| P202         | Do not handle until all safety precautions have been read and understood.   |
| P210         | Keep away from heat/sparks/open flames/hot surfaces No smoking.   |
| P260         | Do not breathe dust/fume/gas/mist/vapours/spray.  |
| P264         | Wash hands thoroughly after handling.   |
| P280         | Wear protective gloves/protective clothing/eye protection/<br>face protection.  |
| P284         | Wear respiratory protection.  |
| P304+340     | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                    |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. |
| P308+313     | IF exposed or concerned: Get medical advice/attention   |
| P314         | Get medical advice/attention if you feel unwell.  |
| P332+313     | If skin irritation occurs: Get medical advice/attention.  |
| P403+233     | Store in a well-ventilated place. Keep container tightly closed.  |

## 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

### 3.2 Mixtures

Hazardous ingredients

Name According to EEC EINEC No. CAS-No. % Classifications

| STYRENE                    | 202-851-5 | 100-42-5   | 25 - <50   | H226-315-319-332-361d-372 | Acute Tox. 4 Inhalation, Eye<br>Irrit. 2, Flam. Liq. 3, Repr. 2,<br>Skin Irrit. 2, STOT RE 1 |
|----------------------------|-----------|------------|------------|---------------------------|--|
| MICA                       | 310-127-6 | 12001-26-2 | 2.5 - <10  | H319-335                  | Eye Irrit. 2, STOT SE 3 RTI  |
| TITANIUM DIOXIDE           | 236-675-5 | 13463-67-7 | 2.5 - <10  |                           |  |
| METHACRYLIC ACID           | 201-204-4 | 79-41-4    | 1.0 - <2.5 | H227-302-311-314-331-335  |  |
| MICROCRYSTALLINE<br>SILICA | 238-878-4 | 14808-60-7 | 0.1 - <1.0 | H350-372                  | Carc. 1A, STOT RE 1  |

| CAS-No.    | M-Factors |
|------------|-----------|
| 100-42-5   | 0         |
| 12001-26-2 | 0         |
| 13463-67-7 | 0         |
| 79-41-4    | 0         |
| 14808-60-7 | 0         |

**Remarks:** CAS No 13463-67-7: Note 10

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

### 4. First-aid Measures

### 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

# 5. Fire-fighting Measures

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

### FOR SAFETY REASONS NOT TO BE USED: No Information

### 5.2 Special hazards arising from the substance or mixture

No Information

### 5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

## SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

## Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

No Information

## 7. Handling and Storage

## 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES:** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

**STORAGE CONDITIONS:** Inhibitor levels should be maintained. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

| <u>Name</u>             | CAS-No.    | ACGIH TWA  | ACGIH STEL       | ACGIH Ceiling |
|-------------------------|------------|------------|------------------|---------------|
| STYRENE                 | 100-42-5   | 10 PPM     | 20 PPM           | N/E           |
| MICA                    | 12001-26-2 | 3 MGM3     | N/E              | N/E           |
| TITANIUM DIOXIDE        | 13463-67-7 | 10 mg/m3   | N/E              | N/E           |
| METHACRYLIC ACID        | 79-41-4    | 20 PPM     | N/E              | N/E           |
| MICROCRYSTALLINE SILICA | 14808-60-7 | 0.025 MGM3 | N/E              | N/E           |
| <u>Name</u>             | CAS-No.    | OSHA P     | EL OSHA S        | <u>TEL</u>    |
| STYRENE                 | 100-42-5   | 215 MGM3   | , 50 PPM425 MGM3 | 3, 100        |

12001-26-2 20. MPPCF **MICA** N/E 15 MGM3 TITANIUM DIOXIDE 13463-67-7 N/E 70 MGM3, 20 PPM METHACRYLIC ACID 79-41-4 N/F 0.05 MGM3 MICROCRYSTALLINE SILICA 14808-60-7 N/E

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

### 8.2 Exposure controls

### **Personal Protection**

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance: Viscous Grey Liquid

Physical State Liquid

Odor Styrene

Odor threshold N/D

pH N/D

Melting point / freezing point (°C) N/D

Boiling point/range (°C) 212 F (100 C) - 400 F (204 C)

Flash Point (°C) 88F (31C)

Evaporation rate Slower Than Ether

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

limits

0.6 - 12.0

Vapour Pressure, mmHg N/D

Vapour density Heavier than Air
Relative density Not determined

Solubility in / Miscibility with water N/D

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Not determined

**Viscosity** Unknown

Explosive properties Not determined

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: 27

Specific Gravity (g/cm3) 1.29

# 10. Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

### 10.4 Conditions to avoid

Heat, flames and sparks.

## 10.5 Incompatible materials

Strong oxidizing agents.

## 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: N/D Inhalation LC50: N/D

Irritation: Eye Irritation, category 2A; Skin Irritation, category 2

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Carcinogenicity, category 1A

Mutagenicity: Unknown

**Toxicity for reproduction:** Reproductive Toxicity, category 2

STOT-single exposure: Unknown

STOT-repeated exposure: STOT, repeated exposure, category 1

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name           | Oral LD50                  | Dermal LD50                   | Vapor LC50                  | Gas LC50          | Dust/Mist<br>LC50 |
|------------|-------------------------|----------------------------|-------------------------------|-----------------------------|-------------------|-------------------|
| 100-42-5   | STYRENE                 | 2650 mg/kg,<br>oral, rat   | >2000 mg/kg,<br>dermal, rat   | 2800 ppm /<br>4hr, inh, rat | 0.000             | 0.000             |
| 12001-26-2 | MICA                    | Not Available              | Not Available                 | Not Available               | 0.000             | 0.000             |
| 13463-67-7 | TITANIUM DIOXIDE        | 25000 mg/kg,<br>oral (rat) | Not Available                 | Not Available               | No<br>Information | No<br>Information |
| 79-41-4    | METHACRYLIC ACID        | 1320 mg/kg,<br>oral, rat   | 1000 mg/kg,<br>dermal, rabbit | 7.1 mg/L / 4h<br>rat, inh   | 0.000             | 0.000             |
| 14808-60-7 | MICROCRYSTALLINE SILICA | 22500 mg/kg                | Not Available                 | Not Available               | 0.000             | 0.000             |

### Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

# 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): Unknown Unknown IC50 72hr (Algae): Unknown LC50 96hr (fish):

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: Unknown

| CAS-No.    | Chemical Name           | EC50 48hr                   | IC50 72hr              | LC50 96hr                    |
|------------|-------------------------|-----------------------------|------------------------|------------------------------|
| 100-42-5   | STYRENE                 | 4.7 mg/l (daphnia)          | 4.9 mg/l (Green Algae) | 4 - 10 mg/l (fathead minnow) |
| 12001-26-2 | MICA                    | No information              | No information         | No information               |
| 13463-67-7 | TITANIUM DIOXIDE        | No information              | No information         | No information               |
| 79-41-4    | METHACRYLIC ACID        | 130 mg/L (Daphnia<br>Magna) | 20 mg/L (Green Algae)  | 85 mg/L (Rainbow Trout)      |
| 14808-60-7 | MICROCRYSTALLINE SILICA | No information              | No information         | No information               |

# 13. Disposal Considerations

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## **Transport Information**

| 14.1 | UN number                    | UN 1263 |
|------|------------------------------|---------|
| 14.2 | UN proper shipping name      | Paint   |
|      | Technical name               | N/A     |
| 14.3 | Transport hazard class(es)   | 3       |
|      | Subsidiary shipping hazard   | N/A     |
| 14.4 | Packing group                | III     |
| 14.5 | Environmental hazards        | Unknown |
| 14.6 | Special precautions for user | Unknown |
|      |                              |         |

EmS-No.: F-E, S-E Unknown

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

# 15. Regulatory Information

Safety, health and environmental regulations/legislation for the substance or mixture:

## U.S. Federal Regulations: As follows -

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> <u>%</u>

STYRENE 100-42-5 28.02

### **Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.DIMETHYLANILINE121-69-7

U.S. State Regulations: As follows -

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

VINYL ESTER RESIN TRADE SECRET GLASS OXIDE 65997-17-3

### Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

VINYL ESTER RESIN TRADE SECRET GLASS OXIDE 65997-17-3 FLY ASH 68131-74-8

### **CALIFORNIA PROPOSITION 65**

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

## International Regulations: As follows -

## \* Canadian DSL:

No Information

### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour. H227 Combustible liquid H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H319 Causes serious eye irritation. Toxic if inhaled. H331 H332 Harmful if inhaled. May cause respiratory irritation. H335 H350 May cause cancer. H361D Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

### Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.