

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

Product Identifier 144PB1NL 12/05/2022 **Revision Date:**

Supercedes Date:

05/01/2022

PLASITE 7159 PART **Product Name:**

В

Relevant identified uses of the

substance or mixture and uses

advised against

Component of

multicomponent industrial coatings - Industrial use.

Details of the supplier of the safety data sheet 1.3

Carboline Global Inc. Manufacturer:

2150 Schuetz Road St. Louis, MO USA 63146

Regulatory / Technical Information: Contact Carboline Technical Services at

1-800-848-4645

Schlereth, Ken - regulatory@carboline.com **Datasheet Produced by:**

CHEMTREC 1-800-424-9300 (Inside US) 1.4 Emergency telephone number:

CHEMTREC +1 703 5273887 (Outside US)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Dermal, category 4 Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Acute, category 1 Hazardous to the aquatic environment, Chronic, category 1 Carcinogenicity, category 1A STOT, repeated exposure, category 1 Skin Corrosion, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

SALICYLIC ACID, BENZYL ALCOHOL, MICROCRYSTALLINE SILICA, METHYLENEOXIDE, POLYMER WITH BENZENAMINE HYDROGENATED

HAZARD STATEMENTS

Acute Toxicity, Dermal, category 4 Skin Corrosion, category 1 Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A	H312 H314-1 H332 H350-1A	Harmful in contact with skin. Causes severe skin burns and eye damage. Harmful if inhaled. May cause cancer.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Acute, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, Chronic, category 1	H410	Very toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.

P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302	IF ON SKIN:
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P352	Wash with plenty of soap and water.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous	ingradiante
nazaruous	iiigi eulei ilo

•					
Name According to EEC MICROCRYSTALLINE SILICA	EINEC No. 238-878-4	<u>CAS-No.</u> 14808-60-7	<u>%</u> 25 - <50	<u>Classifications</u> H350-372	Carc. 1A, STOT RE 1
ZINC PHOSPHATE	231-944-3	7779-90-0	25 - <50	H400-410	
METHYLENEOXIDE, POLYMER WITH BENZENAMINE HYDROGENATED	603-894-6	135108-88-2	10 - <25	H302-312-314-373	Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Skin Corr. 1, STOT RE 2
BENZYL ALCOHOL	202-859-9	100-51-6	10 - <25	H302-312-319-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2
PROPYLENE GLYCOL MONOMETHYL ETHER	203-539-1	107-98-2	1.0 - <2.5	H226-319-332-336	Acute Tox. 4 Inhalation, Eye Irrit. 2, Flam. Liq. 3, STOT SE 3 NE
SALICYLIC ACID	200-712-3	69-72-7	1.0 - <2.5	H302-318-361	Acute Tox. 4 Oral, Eye Dam. 1, Repr. 2
TOLUENE	203-625-9	108-88-3	1.0 - <2.5	H225-304-315-319-332-335-336 -361-370-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 1, STOT SE 3 NE, STOT SE 3 RTI

<u>CAS-No.</u>	M-Factors
14808-60-7	0
7779-90-0	0
135108-88-2	0
100-51-6	0
107-98-2	0
69-72-7	0
108-88-3	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. **AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
MICROCRYSTALLINE SILICA	14808-60-7	0.025 MGM3	N/E	N/E
ZINC PHOSPHATE	7779-90-0	N/E	N/E	N/E
METHYLENEOXIDE, POLYMER WITH BENZENAMINE HYDROGENATED	135108-88-2	N/E	N/E	N/E
BENZYL ALCOHOL	100-51-6	N/E	N/E	N/E
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	50 PPM	100 PPM	N/E
SALICYLIC ACID	69-72-7	N/E	N/E	N/E
TOLUENE	108-88-3	20 PPM	N/E	N/E
<u>Name</u>	CAS-No.	OSHA PEI	OSHA ST	<u>EL</u>
MICROCRYSTALLINE SILICA	14808-60-7	0.05 MGM3	N/E	
ZINC PHOSPHATE	7779-90-0	N/E	N/E	
METHYLENEOXIDE, POLYMER WITH BENZENAMINE HYDROGENATED	135108-88-2	N/E	N/E	
BENZYL ALCOHOL	100-51-6	N/E	N/E	
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	360 MGM3, 1	00 PP 5/4 0 MGM3 PPM	, 150
SALICYLIC ACID	69-72-7	N/E	N/E	
TOLUENE	108-88-3	200 ppm	560 MGM3 PPM	, 150

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Light Amber Liquid

Physical State Liquid

Odor Ammonical

 Odor threshold
 N/D

 pH
 N/D

 Melting point / freezing point (°C)
 N/D

Boiling point/range (°C) 232 F (111 C) - 420 F (216 C)

Flash Point (°C) 219F (104C)

Evaporation rate Slower Than Ether

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive 1.1 - 13.0

limits

Vapour Pressure, mmHg N/D

Vapour density Heavier than Air
Relative density Not determined

Solubility in / Miscibility with water N/D

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity Unknown

Explosive properties Not determined

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: 285
Specific Gravity (g/cm3) 1.72

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: N/D Inhalation LC50: N/D

Irritation: Unknown

Corrosivity: Skin Corrosion, category 1

Sensitization: Skin Sensitizer, category 1

Repeated dose toxicity: STOT, repeated exposure, category 1

Carcinogenicity: Carcinogenicity, category 1A

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: Unknown

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
14808-60-7	MICROCRYSTALLINE SILICA	22500 mg/kg	Not Available	Not Available	0.000	0.000
7779-90-0	ZINC PHOSPHATE	3846mg/kg, oral rat	Not Available	Not Available	0.000	11.54 mg/l
135108-88-2	METHYLENEOXIDE, POLYMER WITH BENZENAMINE HYDROGENATED	2000 mg/kg, oral, rat		Not Available	0.000	0.000
100-51-6	BENZYL ALCOHOL	1230 mg/kg rat, oral	2000 mg/kg, dermal, rabbit	4176 mg/l / 4h, Inh, Rat		
107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	4016 mg/kg, oral, rat	13536 mg/kg, dermal, rabbit	10000 ppm/4hrs rat, inhalation	0.000	0.000
69-72-7	SALICYLIC ACID	891 mg/kg, oral, rat	>2000 mg.kg, dermal, rat	900 mg/m3 1hr, inh, rat	0.000	0.000
108-88-3	TOLUENE	5000 mg/kg rat oral	12267 mg/kg, dermal, rabbit	8000 ppm/4 hrs, rat, inhalation	0.000	0.000

Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):
Unknown
Unknown
Unknown
Unknown
Unknown
Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

12.4 Mobility in soil: Unknown

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: Unknown

CAS-No.	Chemical Name	EC50 48hr	<u>IC50 72hr</u>	LC50 96hr
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information
7779-90-0	ZINC PHOSPHATE	0.04 - 0.86 mg/l (Daphnia Magna)	0.136 - 0.150 mg/l (Selenastrum capricornutum)	0.14 - 0.26 mg/l (Rainbow Trout)
135108-88-2	METHYLENEOXIDE, POLYMER WITH BENZENAMINE HYDROGENATED	15.4 mg/l (Daphnia Magna)	43.9 mg/l (Algae)	63 mg/l Guppy (Poecilia reticulata)
100-51-6	BENZYL ALCOHOL	230 mg/l (Daphnia)	700 mg/l (Algae)	10 mg/l (Fish)
107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	23300 mg/l (Water flea)	No information	20800 mg/l (Fish)
69-72-7	SALICYLIC ACID	No information	No information	No information
108-88-3	TOLUENE	6 mg/l (Daphnia magna)	12.5 mg/L (Algae)	5.8 mg/L (Fish)

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN3082

14.2 UN proper shipping name Environmentally Hazardous Substance, Liquid, NOS

Technical name (Zinc Phosphate)

14.3 Transport hazard class(es) 9

Subsidiary shipping hazard N/A

14.4 Packing group PGIII

14.5 Environmental hazardsMarine Pollutant: Yes (Zinc Phosphate)

14.6 Special precautions for user Unknown EmS-No.: F-A, S-F

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Unknown

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

 Chemical Name
 CAS-No.
 %

 ZINC PHOSPHATE
 7779-90-0
 26.669

 TOLUENE
 108-88-3
 1.01544

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u> <u>CAS-No.</u>

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.