

Safety Data Sheet

[®] Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	218FB1NL	Revision Date:	02/27/2023
	Product Name:	CARBOWELD 17 FG PART B	Supercedes Date:	12/06/2022
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.		
1.3	Details of the supplier of the safety	data sheet		
	Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
	Datasheet Produced by:	Beebe, Hayli - regulatory@carboline.com		
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-68	1-6669	

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 3 Eye Irritation, category 2 Flammable Liquid, category 2 STOT, single exposure, category 3, NE

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

ISOPROPANOL, ETHYL SILICATE, PROPYLENE GLYCOL MONOMETHYL ETHER, ETHYL POLYSILICATE

P261 P273

P280

P304+340

P403+233

P305+351+338

HAZARD STATEMENTS

Flammable Liquid, category 2 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 STOT, single exposure, category 3, NE Hazardous to the aquatic environment, Chronic, category 3	H225 H319 H332 H336 H412	Highly flammable liquid and vapour. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES	P210	Keep away from heat/sparks/open flames/hot surfaces N
	P235	smoking. Keep cool.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/

IF INHALED: Remove victim to fresh air and keep at rest in a

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so.

Store in a well-ventilated place. Keep container tightly

Avoid release to the environment.

position comfortable for breathing.

face protection.

Continue rinsing.

closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

Unknown

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients								
Name According to EEC	<u>EINEC No.</u> 200-661-7	<u>CAS-No.</u> 67-63-0	<u>%</u> 50 - <75	Classifications H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE			
ETHYL ALCOHOL	200-578-6	64-17-5	10 - <25	H225	Flam. Liq. 2			
ETHYL POLYSILICATE	234-324-0	11099-06-2	10 - <25	H319-332-335-411	Acute Tox. 4 Inhalation, Aquatic Chronic 2, Eye Irrit. 2, STOT SE 3 RTI			

No

PROPYLENE GLYCOL MONOMETHYL ETHER	203-539-1	107-98-2	2.5 - <10	H226-319-332-336	Acute Tox. 4 Inhalation, Eye Irrit. 2, Flam. Liq. 3, STOT SE 3 NE
ETHYL SILICATE	201-083-8	78-10-4	1.0 - <2.5	H226-319-331-335	Acute Tox. 3 Inhalation, Eye Irrit. 2, Flam. Liq. 3, STOT SE 3 RTI

CAS-No.	M-Factors
67-63-0	0
64-17-5	0
11099-06-2	0
107-98-2	0
78-10-4	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers /

tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
ISOPROPANOL	67-63-0	200 PPM	400 PPM	N/E
ETHYL ALCOHOL	64-17-5	N/E	1000 PPM	N/E
ETHYL POLYSILICATE	11099-06-2	N/E	N/E	N/E
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	50 PPM	100 PPM	N/E
ETHYL SILICATE	78-10-4	10 PPM	N/E	N/E

Name	CAS-No.	OSHA PEL	<u>OSHA STEL</u>
ISOPROPANOL	67-63-0	980 MGM3, 400 PPM	1225 MGM3, 500 PPM
ETHYL ALCOHOL	64-17-5	1900 MGM3, 1000 PPM	N/E
ETHYL POLYSILICATE	11099-06-2	N/E	N/E
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	360 MGM3, 100 PP 5 4	40 MGM3, 150 PPM
ETHYL SILICATE	78-10-4	85 MGM3, 10 PPM	N/E

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	s Clear Liquid
	Physical State	Liquid
	Odor	Solvent
	Odor threshold	N/D
	рН	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	173 F (78 C) - 336 F (169 C)
	Flash Point (°C)	45F (7C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits	1.8 - 19.0
	Vapour Pressure, mmHg	N/D
	Vapour density	Heavier than Air

	Relative density	Not determined
	Solubility in / Miscibility with water	N/D
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Unknown
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/l:	631
	Specific Gravity (g/cm3)	0.88

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1	Information on toxicological eff	ects			
	Acute Toxicity:				
	Oral LD50:	N/D			
	Inhalation LC50:	N/D			
	Irritation:	Eye Irritation, category 2A			
	Corrosivity:	Unknown			
	Sensitization:	Unknown			
	Repeated dose toxicity:	Unknown			
	Carcinogenicity:	Unknown			
	Mutagenicity:	Unknown			
	Toxicity for reproduction:	Unknown			
	STOT-single exposure:	STOT, single exposure, category 3, NE			
	STOT-repeated exposure:	Unknown			
	Aspiration hazard:	Unknown			

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
67-63-0	ISOPROPANOL	4720 mg/kg rat, oral	12800 mg/kg, dermal, rabbit	22500 ppm/8hrs rat, inhalation	0.000	0.000
64-17-5	ETHYL ALCOHOL	7060 mg/kg, oral, rat	No Information	20000 ppm/10 hrs, rat, inhalation	No Information	No Information
11099-06-2	ETHYL POLYSILICATE	Not Available		Not Available	0.000	0.000
107-98-2	PROPYLENE GLYCOL MONOMETHYL ETHER	4016 mg/kg, oral, rat	13536 mg/kg, dermal, rabbit	10000 ppm/4hrs rat, inhalation	0.000	0.000
78-10-4	ETHYL SILICATE	>2000mg/kg rat, oral		>7.5 mg/L 4 hrs. rat, inhalation	0.000	0.000

Additional Information:

No Information

12.	Ecolo	ogical Information				
12.1	Toxici	ty:				
	EC	50 48hr (Daphnia):	Unknov	vn		
	IC5	0 72hr (Algae):	Unknov	vn		
	LC5	50 96hr (fish):	Unknov	vn		
12.2	Persis	tence and degradability:	Unknov	wn		
12.3	Bioaco	cumulative potential:	Unknov	vn		
12.4	Mobilit	ty in soil:	Unknov	vn		
12.5		s of PBT and vPvB sment:	Unknov	vn		
12.6	Other	adverse effects:	Unknov	wn		
<u>CAS-N</u>	<u>lo.</u>	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
67-63	-0	ISOPROPANOL		13299 mg/l (Daphnia Magna)	>1000 m/gL (desmodesmus subspicatus)	9640 mg/L (pimphales promelas)
64-17-	-5	ETHYL ALCOHOL		2 mg/l (Daphnia Magna)	No information	42 mg/l (fish)
11099	-06-2	ETHYL POLYSILICATE		No information	No information	No information
107-98	8-2	PROPYLENE GLYCOL MONOMETHY	L	23300 mg/l (Water flea)	No information	20800 mg/l (Fish)
78-10-	-4	ETHYL SILICATE		No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information				
14.1	UN number	UN1263		
14.2	UN proper shipping name	Paint		
	Technical name	No Information		
14.3	Transport hazard class(es)	3		
	Subsidiary shipping hazard	No Information		
14.4	Packing group	II		
14.5	Environmental hazards	Unknown		
14.6	Special precautions for user	Unknown		
	EmS-No.:	F-E, S-E		
	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown		
15.	Regulatory Information			

Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	<u>%</u>
HYDROGEN CHLORIDE	7647-01-0	0.0314

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.	
WATER	7732-18-5	
Bonnovlyonia Dight Ta Know		

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
WATER	7732-18-5

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.