

## **Safety Data Sheet**

## Prepared in Accordance with HCS 29 C.F.R. 1910.1200

## 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 4700S1NL Revision Date: 09/08/2025

Product Name: THERMALINE 4700 Supercedes Date: 12/06/2022

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Monocomponent industrial coating - Industrial use.

1.3 Details of the supplier of the safety data sheet

Manufacturer: Carboline Global Inc.

2150 Schuetz Road St. Louis, MO USA 63146

Regulatory / Technical Information: Contact Carboline Technical Services at

1-800-848-4645

Datasheet Produced by: Schlereth, Ken - regulatory@carboline.com

1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside ÚS)

HEALTH - Pittsburgh Poison Control 1-412-681-6669

## 2. Hazard Identification

## 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Hazardous to the aquatic environment, Chronic, category 3
Eye Irritation, category 2
Flammable Liquid, category 3
Skin Irritation, category 2

#### 2.2 Label elements

## Symbol(s) of Product



## Signal Word

Warning

## Named Chemicals on Label

ORTHO-XYLENE, ETHYL BENZENE, PARA-XYLENE, META-XYLENE, CHROME ANTIMONY COMPOUND

#### **HAZARD STATEMENTS**

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do so. Continue rinsing.

P332+313 If skin irritation occurs: Get medical advice/attention. P403+233 Store in a well-ventilated place. Keep container tightly

closed.

#### 2.3 Other hazards

No Information

#### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

#### **Mixtures**

## Hazardous ingredients

Name According to EEC	EINEC No.	CAS-No.	<u>%</u>	Classifications
TITANIUM DIOXIDE	236-675-5	13463-67-7	30 - <60	
NICKEL ANTIMONY COMPOUND	232-353-3	8007-18-9	10 - <30	
COBALT COMPOUND	310-193-6	1345-16-0	10 - <30	
COPPER COMPOUND	269-053-7	68186-91-4	10 - <30	

Date Printed: 09/08/20	25				Product: 4700S1NL
META-XYLENE	203-576-3	108-38-3	10 - <30	H226-312-315-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2
CHROME ANTIMONY COMPOUND	269-052-1	68186-90-3	5.0 - <10	H332-411	Acute Tox. 4 Inhalation, Aquatic Chronic 2
PARA-XYLENE	203-396-5	106-42-3	5.0 - <10	H226-312-315-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2
MICA	310-127-6	12001-26-2	5.0 - <10	H319-335	Eye Irrit. 2, STOT SE 3 RTI
ETHYL BENZENE	202-849-4	100-41-4	5.0 - <10	H225-304-332-373-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Flam. Liq. 2, STOT RE 2
ORTHO-XYLENE	202-422-2	95-47-6	1.0 - <5.0	H226-312-315-332	Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Flam. Liq. 3, Skin Irrit. 2
AROMATIC HYDROCARBON	265-198-5	64742-94-5	1.0 - <5.0	H304	Asp. Tox. 1
SOBUTANOL	201-148-0	78-83-1	1.0 - <5.0	H226-315-318-335-336	Eye Dam. 1, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI
AMORPHOUS SILICA	231-545-4	7631-86-9	1.0 - <5.0		
TOLUENE	203-625-9	108-88-3	0.1 - <1.0	H225-304-315-336-361d-370-37 3	Asp. Tox. 1, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT RE 2, STOT SE 1, STOT SE 3 NE
NAPHTHALENE	202-049-5	91-20-3	0.1 - <1.0	H302-351-400-410	Acute Tox. 4 Oral, Aquatic Acute 1, Aquatic Chronic 1, Carc. 2

<u>CAS-No.</u> 13463-67-7

M-Factors

13463-67-7 8007-18-9 1345-16-0 68186-91-4 108-38-3 68186-90-3 106-42-3 12001-26-2 100-41-4 95-47-6 64742-94-5 78-83-1 7631-86-9 108-88-3 91-20-3

Remarks: CAS No 13463-67-7: Note 10

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

## 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. **AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

## 5. Fire-fighting Measures

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire.

#### 5.2 Special hazards arising from the substance or mixture

No Information

## 5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

## 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

No Information

## 7. Handling and Storage

## 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

## 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	N/E
NICKEL ANTIMONY COMPOUND	8007-18-9	N/E	N/E	N/E
COBALT COMPOUND	1345-16-0	.02 MG/M3	NE	N/E
COPPER COMPOUND	68186-91-4	.5 MG/M3	NE	N/E
META-XYLENE	108-38-3	100 PPM	150 PPM	N/E
CHROME ANTIMONY COMPOUND	68186-90-3	N/E	N/E	N/E
PARA-XYLENE	106-42-3	100 PPM	150 PPM	N/E
MICA	12001-26-2	0.1 MGM3	N/E	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
ORTHO-XYLENE	95-47-6	100 PPM	150 PPM	N/E
AROMATIC HYDROCARBON	64742-94-5	300.0 PPM	N/E	N/E
ISOBUTANOL	78-83-1	50 PPM	N/E	N/E
AMORPHOUS SILICA	7631-86-9	10.0 MG/M3	N/E	N/E
TOLUENE	108-88-3	20 PPM	N/E	N/E
NAPHTHALENE	91-20-3	10 PPM	15 ppm	N/E

<u>Name</u>	CAS-No.	OSHA PEL	OSHA STEL
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E
NICKEL ANTIMONY COMPOUND	8007-18-9	1 mg/m3	N/E
COBALT COMPOUND	1345-16-0	.05 MG/M3	N/E
COPPER COMPOUND	68186-91-4	0.5 MG/M3	N/E
META-XYLENE	108-38-3	100.00 PPM	N/E
CHROME ANTIMONY COMPOUND	68186-90-3	N/E	N/E
PARA-XYLENE	106-42-3	100.00 PPM	N/E
MICA	12001-26-2	20. MPPCF	N/E
ETHYL BENZENE	100-41-4	435 MGM3, 100 PPM	545 MGM3, 125 PPM
ORTHO-XYLENE	95-47-6	100.00 PPM	N/E

AROMATIC HYDROCARBON	64742-94-5	500.0 PPM	N/E
ISOBUTANOL	78-83-1	150 MGM3, 50 PPM	N/E
AMORPHOUS SILICA	7631-86-9	15.0 mg/m3	N/E
TOLUENE	108-88-3	200 ppm 5	560 MGM3, 150 PPM
NAPHTHALENE	91-20-3	50 MGM3, 10 PPM	75 MGM3, 15 PPM

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

#### 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier.

**BODY PROTECTION:** Lightweight protective clothing **OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas

## 9. Physical and Chemical Properties

#### 9.1 Information on basic physical and chemical properties

Appearance: Viscous Liquid, Various Colors

Physical State Liquid
Odor Solvent
Odor threshold N/D
pH N/D
Melting point / freezing point (°C) N/D

Boiling point/range (°C) 149 F (65 C) - 424 F (218 C)

Flash Point (°C) 83F (28C)

Evaporation rate Slower Than Ether

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive 0.9 - 10.9

limits

Vapour Pressure, mmHg N/D

Vapour density Heavier than Air
Relative density Not determined

Solubility in / Miscibility with water N/D

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C) Not determined

**Viscosity** Unknown

Explosive properties Not determined

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: 456

Specific Gravity (g/cm3) app. 1.30

## 10. Stability and Reactivity

## 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Heat, flames and sparks.

## 10.5 Incompatible materials

Strong oxidizing agents.

## 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## 11. Toxicological Information

## 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: N/D Inhalation LC50: N/D

Irritation: Eye Irritation, category 2A; Skin Irritation, category 2

Corrosivity: Unknown

Sensitization: Unknown

Repeated dose toxicity: Unknown

Carcinogenicity: Carcinogenicity, category 2

Mutagenicity: Unknown

Toxicity for reproduction: Unknown

STOT-single exposure: Unknown

STOT-repeated exposure: Unknown

Aspiration hazard: Unknown

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	No Information	No Information	No Information	No Information
8007-18-9	NICKEL ANTIMONY COMPOUND	10000 mg/kg oral rat		Not Available	0.000	0.000
1345-16-0	COBALT COMPOUND	10001 MG/ KG, ORAL, RAT		NOT AVAILABLE	0.000	0.000
68186-91-4	COPPER COMPOUND	10001 MG/L, ORAL, RAT		NOT AVAILABLE	0.000	0.000
108-38-3	META-XYLENE	No Information	No Information	No Information	No Information	No Information
68186-90-3	CHROME ANTIMONY COMPOUND	>10000 MG/ KG, ORAL, RAT		NOT AVAILABLE	0.000	0.000
106-42-3	PARA-XYLENE	No Information	No Information	No Information	No Information	No Information
12001-26-2	MICA	No Information	No Information	No Information	No Information	No Information
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	No Information	No Information

95-47-6	ORTHO-XYLENE	No Information	No Information	No Information	No Information	No Information
64742-94-5	AROMATIC HYDROCARBON	5001 mg/kg (rat)	2001 mg/kg (rabbit)	Not Available	0.000	0.000
78-83-1	ISOBUTANOL	2500 mg/kg, oral, rat	3404 mg/kg, dermal, rat	8000 ppm/4h, rat, INH	0.000	0.000
108-88-3	TOLUENE	5000 mg/kg rat oral	12267 mg/kg, dermal, rabbit	8000 ppm/4 hrs, rat, inhalation	No Information	No Information
91-20-3	NAPHTHALENE	Not Available	Not Available	Not Available	0.000	0.000

#### Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

## 12. Ecological Information

## 12.1 Toxicity:

EC50 48hr (Daphnia):
Unknown
Unknown
Unknown
Unknown
Unknown

12.2 Persistence and degradability: Unknown

12.3 Bioaccumulative potential: Unknown

**12.4 Mobility in soil:** Unknown

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: Unknown

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
8007-18-9	NICKEL ANTIMONY COMPOUND	No information	No information	No information
1345-16-0	COBALT COMPOUND	No information	No information	No information
68186-91-4	COPPER COMPOUND	No information	No information	No information
108-38-3	META-XYLENE	No information	No information	No information
68186-90-3	CHROME ANTIMONY COMPOUND	No information	No information	No information
106-42-3	PARA-XYLENE	No information	No information	No information
12001-26-2	MICA	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)
95-47-6	ORTHO-XYLENE	No information	No information	No information
64742-94-5	AROMATIC HYDROCARBON	No information	No information	No information

78-	83-1	ISOBUTANOL	1300 mg/l (Daphnia Magna)	No information	11200-01520g/L (Oncorhynchus mykiss)
763	31-86-9	AMORPHOUS SILICA	No information	10000 mg/l (Algae)	10000 mg/l (Zebra fish)
108	3-88-3	TOLUENE	6 mg/l (Daphnia magna)	12.5 mg/L (Algae)	5.8 mg/L (Fish)
91-	20-3	NAPHTHALENE	No information	No information	No information

## 13. Disposal Considerations

I3.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	14. Transport Information				
14.1	UN number	UN1263			
14.2	UN proper shipping name	Paint			
	Technical name	N/A			
14.3	Transport hazard class(es)	3			
	Subsidiary shipping hazard	N/A			
14.4	Packing group	III			
14.5	Environmental hazards	Unknown			
14.6	Special precautions for user	Unknown			
	EmS-No.:	F-E, S-E			
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown			

## 15. Regulatory Information

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

## **CERCLA - Sara Hazard Category**

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation

## Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	CAS-No.	<u>%</u>
NICKEL ANTIMONY COMPOUND	8007-18-9	27.51
COBALT COMPOUND	1345-16-0	25.59
COPPER COMPOUND	68186-91-4	18.62
META-XYLENE	108-38-3	15.83
CHROME ANTIMONY COMPOUND	68186-90-3	8.94
PARA-XYLENE	106-42-3	6.88
ETHYL BENZENE	100-41-4	6.54
ORTHO-XYLENE	95-47-6	4.99
NAPHTHALENE	91-20-3	0.13

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

## **Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## U.S. State Regulations: As follows -

## New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

SILICONE RESIN TRADE SECRET

## Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

SILICONE RESIN TRADE SECRET IRON OXIDE 1309-37-1

## **CALIFORNIA PROPOSITION 65**

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

## International Regulations: As follows -

## \* Canadian DSL:

All chemical ingredients included on inventory (DSL)

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## Other Information

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

H361D Suspected of damaging the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.

H410
 H411
 H411
 Toxic to aquatic life with long lasting effects.
 H412
 Harmful to aquatic life with long lasting effects.

#### Reasons for revision

#### No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.