

Carbocoat 8215 VOC

Direct-to-Metal (Single Coat) Enamel for Marine Use

Description

This marine enamel is a high solids, quick-dry, general purpose, single-coat, alkyd enamel that is used as a self-priming finish coat. Carbocoat 8215 VOC has exceptional application characteristics, fast dry properties and very good corrosion protection as a direct-to-metal coating. It replaces a two-coat (primer/finish) system as a versatile marine coating for a variety of applications including new construction or maintenance. It meets the 340 g/l VOC limit and has very low HAP's at 0.6 lbs/solid gal suitable for use in today's shipyards.

Specification Data

- ❖ *Solids by Volume: 53%*
- ❖ *DFT: 2-3 mils*
- ❖ *VOC: 336 g/l*
- ❖ *HAPs: 0.06 lbs/solid gal*
- ❖ *Surface Prep: Minimum SSPC SP3*
- ❖ *Finish: Gloss*
- ❖ *Dry to touch @75°F: 30 minutes*
- ❖ *Dry to handle @75°F: 2 hours*
- ❖ *Dry hard @75°F: 24 hours*
- ❖ *Application to 35°F*



Features

- ✓ Custom colors; Rapid Tint
- ✓ Smooth, attractive, gloss finish
- ✓ Single-coat protection
- ✓ Direct-to-metal application
- ✓ Good weatherability
- ✓ Good gloss and color retention
- ✓ HAP's = 0.6 lbs/solid gallon
- ✓ Contains corrosion inhibitor
- ✓ Excellent application properties
- ✓ Quick dry to handle times
- ✓ Good flexibility
- ✓ Impact and abrasion resistant
- ✓ VOC-compliant for marine yards