

Safety Data Sheet

<sup>®</sup> Prepared in Accordance with HCS 29 C.F.R. 1910.1200

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	8843B1NL	Revision Date: 12/05/2	
	Product Name:	URETHANE CONVERTER 8843	Supercedes Date:	09/14/2022
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.		
1.3	Details of the supplier of the safety	data sheet		
	Manufacturer:	Carboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
	Datasheet Produced by:	Schlereth, Ken - regulatory@carboline.com		
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-68	1-6669	

# 2. Hazard Identification

# 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 3 Eye Irritation, category 2 Flammable Liquid, category 2 STOT, single exposure, category 3, RTI Skin Sensitizer, category 1

# 2.2 Label elements

# Symbol(s) of Product



# Signal Word

Danger

# Named Chemicals on Label

HOMOPOLYMER OF HDI, AROMATIC HYDROCARBON

# HAZARD STATEMENTS

Flammable Liquid, category 2 Skin Sensitizer, category 1 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 STOT, single exposure, category 3, RTI Hazardous to the aquatic environment, Chronic, category 3 <b>PRECAUTION PHRASES</b>	H225 H317 H319 H332 H335 H412	Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
	P210	Keep away from heat/sparks/open flames/hot surfaces No
	P235	smoking. Keep cool.
	P235 P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid bleating dustrane/gas/hist/vapodis/spray.
	P280	Wear protective gloves/protective clothing/eye protection/
	. 200	face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.
ADDITIONAL INFORMATION		
	Note_P 64742-95-6	Note P : The classification as a carcinogen or mutagen need not apply; the substance, CAS 64742-95-6, contains less than 0,1 % w/w benzene

# 2.3 Other hazards

No Information

# Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients 3.2 Mixtures

# Hazardous ingredients

Name According to EEC EINEC No. CAS-No.

<u>%</u>

**Classifications** 

#### Date Printed: 06/20/2023

Product: 8843B1NL

Homopolymer of HDI	500-060-2	28182-81-2	75 - 100	H317-332-335	Acute Tox. 4 Inhalation, Skin Sens. 1, STOT SE 3 RTI
METHYL ETHYL KETONE	201-159-0	78-93-3	2.5 - <10	H225-319-336	Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE
N-BUTYL ACETATE	204-658-1	123-86-4	2.5 - <10	H226-336	Flam. Liq. 3, STOT SE 3 NE
AROMATIC HYDROCARBON	265-199-0	64742-95-6	2.5 - <10	H304-315-319-332-335-336-351 -411	Acute Tox. 4 Inhalation, Aquatic Chronic 2, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI
HEXAMETHYLENE DIISOCYANATE	212-485-8	822-06-0	0.1 - <1.0	H302-315-317-319-331-334-335	Acute Tox. 3 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI

CAS-No.	M-Factors
28182-81-2	0
78-93-3	0
123-86-4	0
64742-95-6	0
822-06-0	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

# 4. First-aid Measures

# 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

# 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

# 5. Fire-fighting Measures

# 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Humid air and/or water will produce carbon dioxide which will pressurize the container. Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

# FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

### 5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

# 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

# 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

# 6.4 Reference to other sections

No Information

# 7. Handling and Storage

# 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

# CONDITIONS TO AVOID: Heat, flames and sparks. Exposure to moisture.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

# 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
HOMOPOLYMER OF HDI	28182-81-2	N/E	N/E	N/E
METHYL ETHYL KETONE	78-93-3	200 PPM	300 PPM	N/E

#### Date Printed: 06/20/2023

N-BUTYL ACETATE AROMATIC HYDROCARBON HEXAMETHYLENE DIISOCYANATE	123-86-4 64742-95-6 822-06-0	50 PPM 300.0 PPM 0.005 PPM	150 PPM N/E N/E	N/E N/E N/E
Name	CAS-No.	<u>OSHA PEL</u>	<u>OSHA STE</u>	L
HOMOPOLYMER OF HDI	28182-81-2	N/E	N/E	
METHYL ETHYL KETONE	78-93-3	590 MGM3, 20	0 PP <b>8/8</b> 5 MGM3, 3 PPM	00
N-BUTYL ACETATE	123-86-4	710 MGM3, 15	0 PP <b>9/5</b> 0 MGM3, 2 PPM	200
AROMATIC HYDROCARBON	64742-95-6	500.0 PPM	N/E	
HEXAMETHYLENE DIISOCYANATE	822-06-0	N/E	N/E	

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

#### 8.2 Exposure controls

9.1

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

Information on basic physical and chemical properties Appearance:	Colorless, Mobile Liquid
Physical State	Liquid
Odor	Slight Odor
Odor threshold	N/D
рН	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range (°C)	173 F (78 C) - 545 F (285 C)
Flash Point (°C)	62F (17C)
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined

Upper/lower flammability or explosive

0.9 - 10.1

	0.3 - 10.1
limits	
Vapour Pressure, mmHg	N/D
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined
Other information	
VOC Content g/I:	Refer to Part A MSDS
Specific Gravity (g/cm3)	1.09

# 10. Stability and Reactivity

10.1 Reactivity

9.2

Water reactive

10.2 Chemical stability

Stable under normal conditions.

**10.3 Possibility of hazardous reactions** Hazardous polymerisation does not occur.

# 10.4 Conditions to avoid

Heat, flames and sparks. Exposure to moisture.

# 10.5 Incompatible materials

Never allow product to get in contact with water during storage. Water in the container will lead to increased pressure and risk of explosion. Strong oxidizing agents.

# 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

11.1	C C C C C C C C C C C C C C C C C C C				
	Acute Toxicity:				
	Oral LD50:	N/D			
	Inhalation LC50:	N/D			
	Irritation:	Eye Irritation, category 2			
	Corrosivity:	Unknown			
	Sensitization:	Skin sensitizer and Respiratory sensitizer, category 1			
	Repeated dose toxicity:	Unknown			
	Carcinogenicity:	Unknown			
	Mutagenicity:	Unknown			
	Toxicity for reproduction:	Unknown			
	STOT-single exposure:	STOT, single exposure, category 3, RTI			
	STOT-repeated exposure:	Unknown			
	Aspiration hazard:	Unknown			

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
28182-81-2	HOMOPOLYMER OF HDI	5000 mg/kg, oral, rat	Not Available	390 mg/m3, inhalation, rat	0.000	0.000
78-93-3	METHYL ETHYL KETONE	2194 mg/kg rat, oral	Not Available	34.5 mg/L/ 4 hour rat, inhalation	0.000	0.000
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat		
64742-95-6	AROMATIC HYDROCARBON	4700 mg/kg, oral, rat	Not Available	3670 ppm/8 hours, rat, inhalation	0.000	0.000
822-06-0	HEXAMETHYLENE DIISOCYANATE	710 mg/kg, oral rat	>7000 mg/kg, dermal, rat	23 ppm / 4 hrs	0.000	0.000

# Additional Information:

No Information

12.	Ecol	ogical Information				
12.1	Toxic	ity:				
	EC	50 48hr (Daphnia):	Unkno	wn		
	IC5	i0 72hr (Algae):	Unkno	wn		
	LC	50 96hr (fish):	Unkno	wn		
12.2	Persis	stence and degradability:	Unkno	wn		
12.3	Bioac	cumulative potential:	Unkno	wn		
12.4	Mobil	ity in soil:	Unkno	wn		
12.5 Results of PBT and vPvB assessment:		The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII				
12.6	Other	adverse effects:	Unkno	wn		
<u>CAS-</u>	<u>No.</u>	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
28182	2-81-2	HOMOPOLYMER OF HDI		No Information	No information	No Infomration
78-93	3-3	METHYL ETHYL KETONE		308 mg/l (Daphnia magna)	No information	2993 mg/l (Pimephales promelas)
123-8	36-4	N-BUTYL ACETATE		44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
64742	2-95-6	AROMATIC HYDROCARBON		No information	No information	No information
822-0	06-0	HEXAMETHYLENE DIISOCYANATE		No information	No information	No information

# 13. Disposal Considerations

**13.1** WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14.	Transport Information	
14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	П
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

# 15. Regulatory Information

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

# **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Acute Toxicity (any route of exposure), Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

# Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	CAS-No.	<u>%</u>
HEXAMETHYLENE DIISOCYANATE	822-06-0	0.1866081
ETHYL BENZENE	100-41-4	0.0555159
1,2,4 TRIMETHYLBENZENE	95-63-6	0.046652
CUMENE	98-82-8	0.046652
META-XYLENE	108-38-3	0.0214599
PARA-XYLENE	106-42-3	0.0093304
ORTHO-XYLENE	95-47-6	0.0067645
TOLUENE	108-88-3	0.0002286
BENZENE	71-43-2	4.7E-06

# Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

# U.S. State Regulations: As follows -

# New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product. Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product. CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

# International Regulations: As follows -

# \* Canadian DSL:

All chemical ingredients included on inventory (DSL)

# 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

# Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

### Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Date Printed: 06/20/2023