

Safety Data Sheet

[®] Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

Product Name:STRATHOLINER 7100 PART BSupercedes Date:12/071.2Relevant identified uses of the substance or mixture and uses advised againstComponent of multicomponent industrial coatings - Industrial use.Supercedes Date:12/071.3Details of the supplier of the safetyCarboline Global Inc. 2150 Schuetz Road St. Louis, MO USA 63146Supercedes Date:12/07	12/05/2022						
 1.2 Relevant identified uses of the substance or mixture and uses advised against 1.3 Details of the supplier of the safety data sheet Manufacturer: Carboline Global Inc. 2150 Schuetz Road 	12/07/2018						
Manufacturer: Carboline Global Inc. 2150 Schuetz Road							
2150 Schuetz Road	1.3 Details of the supplier of the safety data sheet						
Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645							
Datasheet Produced by: Schlereth, Ken - regulatory@carboline.com							
1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US) HEALTH - Pittsburgh Poison Control 1-412-681-6669							

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A Eye Irritation, category 2 Flammable Liquid, category 2 Germ Cell Mutagenicity, category 1A STOT, repeated exposure, category 1 Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

ORTHO-XYLENE, ETHYL BENZENE, PARA-XYLENE, META-XYLENE, AMORPHOUS SILICA

HAZARD STATEMENTS

H225 H315 H319 H332 H340-1A H350-1A H372	Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P235	Keep cool.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
	H315 H319 H332 H340-1A H350-1A H372 P201 P202 P210 P235 P260 P264 P264 P280 P284 P304+340 P305+351+338 P308+313 P314 P332+313

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3.	Composition/Information On Ingredients
2.2	Mixturee

<u>%</u>

3.2 Mixtures

```
Hazardous ingredients
```

```
Name According to EEC EINEC No. CAS-No.
```

<u>o.</u>

Classifications

Date Printed: 06/19/2023

Product: 147SB1NL

N-BUTYL ACETATE	204-658-1	123-86-4	10 - <25	H226-336	Flam. Liq. 3, STOT SE 3 NE
AMORPHOUS SILICA	231-545-4	7631-86-9	10 - <25	H335-372	STOT RE 1, STOT SE 3 RTI
VMP NAPHTHA	232-453-7	8032-32-4	2.5 - <10	H304-340-350	
ETHYL BENZENE	202-849-4	100-41-4	2.5 - <10	H225-304-315-319-332-351-373 -412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Carc. 2, Eye Irrit. 2, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2
META-XYLENE	203-576-3	108-38-3	2.5 - <10	H312-315-332	
PARA-XYLENE	203-396-5	106-42-3	2.5 - <10	H304-312-315-332-335-371	
ORTHO-XYLENE	202-422-2	95-47-6	1.0 - <2.5	H312-315-332	
N-BUTANOL	200-751-6	71-36-3	1.0 - <2.5	H226-302-315-318-335-336	Acute Tox. 4 Oral, Eye Dam. 1, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI
CHLORENDIC ACID		115-28-6	0.1 - <1.0	H318-351	

CAS-No.	M-Factors
123-86-4	0
7631-86-9	0
8032-32-4	0
100-41-4	0
108-38-3	0
106-42-3	0
95-47-6	0
71-36-3	0
115-28-6	0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. **AFTER INGESTION:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call

a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
N-BUTYL ACETATE	123-86-4	50 PPM	150 PPM	N/E
AMORPHOUS SILICA	7631-86-9	10.0 MG/M3	N/E	N/E
VMP NAPHTHA	8032-32-4	300 PPM	N/E	N/E
ETHYL BENZENE	100-41-4	20 PPM	125 ppm	
META-XYLENE	108-38-3	100 PPM	150 PPM	N/E
PARA-XYLENE	106-42-3	100 PPM	150 PPM	N/E
ORTHO-XYLENE	95-47-6	100 PPM	150 PPM	N/E
N-BUTANOL	71-36-3	20 PPM	N/E	N/E
CHLORENDIC ACID	115-28-6	N/E	N/E	N/E
Name	CAS-No.	<u>OSHA PE</u>	<u>il osha s</u>	TEL
N-BUTYL ACETATE	123-86-4	710 MGM3,	150 PP 95 0 MGM3 PPM	
AMORPHOUS SILICA	7631-86-9	15.0 mg/m3	N/E	
VMP NAPHTHA	8032-32-4	1350 MGM3 PPM	, 300 1800 MG 400 PP	
ETHYL BENZENE	100-41-4	435 MGM3,	100 PP 5/4 5 MGM3 PPM	
META-XYLENE	108-38-3	100.00 PPM	N/E	
PARA-XYLENE	106-42-3	100.00 PPM	N/E	
ORTHO-XYLENE	95-47-6	100.00 PPM	N/E	
N-BUTANOL	71-36-3	300.0 MG/M	3 N/E	
CHLORENDIC ACID	115-28-6	N/E	N/E	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	s Viscous Liquid, White
	Physical State	Liquid
	Odor	Aromatic
	Odor threshold	Not Determined
	рН	Not Determined
	Melting point / freezing point (°C)	Not Determined
	Boiling point/range (°C)	176 F (80 C) - 334 F (168 C)
	Flash Point (°C)	72°F (22°C)
	Evaporation rate	Slower Than Ether
	Flammability (solid, gas)	N/D
	Upper/lower flammability or explosive limits	0.8 - 11.2
	Vapour Pressure, mmHg	Not Determined
	Vapour density	Heavier than Air
	Relative density	N/D
	Solubility in / Miscibility with water	Not Determined
	Partition coefficient: n-octanol/water	N/D
	Auto-ignition temperature (°C)	N/D
	Decomposition temperature (°C)	N/D
	Viscosity	Not Determined
	Explosive properties	N/D
	Oxidising properties	N/D
9.2	Other information	
	VOC Content g/l:	363
	Specific Gravity (g/cm3)	1.21

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Information on toxicological effects				
Acute Toxicity:				
Oral LD50:	N/D			
Inhalation LC50:	N/D			
Irritation:	No information available.			
Corrosivity:	No information available.			
Sensitization:	No information available.			
Repeated dose toxicity:	No information available.			
Carcinogenicity:	No information available.			
Mutagenicity:	No information available.			
Toxicity for reproduction:	No information available.			
STOT-single exposure:	No Information			
STOT-repeated exposure:	No Information			
Aspiration hazard:	No Information			

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
123-86-4	N-BUTYL ACETATE	10760 mg/kg, rat, oral	14112 mg/kg (rabbit)	21 mg/l/4/h, Inh. rat		
8032-32-4	VMP NAPHTHA	NOT AVAILABLE		NOT AVAILABLE	0.000	0.000
100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	0.000	0.000
108-38-3	META-XYLENE	Not Available	Not Available	Not Available	0.000	0.000
106-42-3	PARA-XYLENE	Not Available	Not Available	Not Available	0.000	0.000
95-47-6	ORTHO-XYLENE	Not Available	Not Available	Not Available	0.000	0.000

71-36-3	N-BUTANOL	790 mg/kg rat, oral	3400 mg/kg, dermal, rabbit	8000 ppm / 4hrs rat, inhalation	0.000	0.000
115-28-6	CHLORENDIC ACID	NOT AVAILABLE		NOT AVAILABLE	0.000	0.000

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

12. Ecological Information

12.1 Toxicity:

8032-32-4

100-41-4

108-38-3

106-42-3

95-47-6

71-36-3

115-28-6

	IC	50 48hr (Daphnia): 50 72hr (Algae): 50 96hr (fish):	No information available. No information available. No information available.			
12.2	Persi	stence and degradability:	e and degradability: No information available.			
12.3	Bioac	cumulative potential:	No information available.			
12.4	Mobil	ity in soil:	No information available.			
12.5		Its of PBT and vPvB ssment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XII			
12.6	Othe	adverse effects:	No information available.			
CAS-	<u>-No.</u>	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
123-8	86-4	N-BUTYL ACETATE		44 mg/l (Daphnia magna)	674.7 mg/L (Green Algae)	18 mg/l (Fathead minnow)
7631·	-86-9	AMORPHOUS SILICA		No information	10000 mg/l (Algae)	10000 mg/l (Zebra fish)

No information

No information

No information

No information

No information

1328 mg/l (Daphnia

Magna)

magna)

1.8 mg/l (Daphnia

No information

No information

No information

No information

225 mg/l (Algae)

No information

No information

No information

No information

No information

No information

1376 mg/l (Fathead minnow)

4.6 mg/l (Green Algae) 4.2 mg/l (Rainbow Trout)

13. Disposal Considerations

N-BUTANOL

VMP NAPHTHA

META-XYLENE

PARA-XYLENE

ORTHO-XYLENE

CHLORENDIC ACID

ETHYL BENZENE

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, 13.1 dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

	Tranoport information	
14.1	UN number	UN1263
14.2	UN proper shipping name	Paint
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	II
14.5	Environmental hazards	No information available.
14.6	Special precautions for user	No information available.
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	<u>%</u>
ETHYL BENZENE	100-41-4	6.7437632
META-XYLENE	108-38-3	5.8608108
PARA-XYLENE	106-42-3	2.5481786
ORTHO-XYLENE	95-47-6	1.8474295
N-BUTANOL	71-36-3	1.4403916
CHLORENDIC ACID	115-28-6	0.857033
TOLUENE	108-88-3	0.0624304
CUMENE	98-82-8	0.0018187
1,2,4 TRIMETHYLBENZENE	95-63-6	0.0018187
BENZENE	71-43-2	0.0012741

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	<u>CAS-No.</u>
POLYESTER RESIN	TRADE SECRET
Pennsylvania Right-To-Know	

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
POLYESTER RESIN	TRADE SECRET
CALIFORNIA PROPOSITION 65	

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory (DSL)

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of

the user to comply with all applicable federal, state, and local laws and regulations.

Date Printed: 06/19/2023