

SELECTION & SPECIFICATION DATA

Generic Type	Specially formulated citric acid solution
Description	<p>Carbozinc (water based) Neutralizing Solution is an organic and biodegradable product designed specifically for use with Carbozinc and Carboweld water-based, inorganic primers, including:</p> <p>Carbozinc 11 WB Carbozinc 18 WB Carboweld 9 WB Carboweld 11 WB Carboweld 14 WB</p> <p>It is an environmentally safe product that will clean, neutralize (lower the surface pH), and degrease the waterbased Carbozinc/weld primers for topcoating. This product does not contain any bleach, chlorinated solvents, phosphates, muriatic or ozone depleting ingredients.</p>
Features	<ul style="list-style-type: none"> • Water-based, biodegradable • Easy to use • Prepares water-based inorganic zincs for topcoating
Color	Clear liquid
Coverage Rate	<p>Approximately 200-250 ft²/gal (4.9-6.1 m²/gal)</p> <p>Apply liberally.</p>

APPLICATION PROCEDURES

General	Apply liberally by brush, roller, pumpstyle sprayer, airless or pressure washer. On vertical surfaces start from the bottom and work up. Wait 2 hours; agitate the surface with scrub brushes or similar and then rinse thoroughly or power wash with clean potable water. Allow to thoroughly dry and check for pH. Optimum pH should be in the 5-7 range.
----------------	---

CLEANUP & SAFETY

Safety	Read and follow all caution statements on this product data sheet and on the SDS for this product. Employ normal workmanlike safety precautions. Solution is corrosive. Wear chemical resistant gloves, apron, footwear, and eye/face protection. Use adequate ventilation. Keep container closed when not in use.
---------------	--

PACKAGING, HANDLING & STORAGE

Shelf Life	<p>36 months at 75 °F (24 °C)</p> <p>*Shelf Life: (actual stated shelf life) when kept at recommended storage conditions and in original unopened containers.</p>
Storage Temperature & Humidity	<p>40-110 °F (4-43 °C)</p> <p>0-90% Relative Humidity</p>
Storage	Store Indoors.
Shipping Weight (Approximate)	<p>5 Gal - 45 lbs (20 kg)</p> <p>50 Gal Drum - 485 lbs (220 kg)</p>

CZ (WB) Neutralizing Solution

PRODUCT DATA SHEET



WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Carboline warrants our products to be free of manufacturing defects in accord with applicable Carboline quality control procedures. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT: (1) APPLIED IN ACCORDANCE WITH CARBOLINE'S SPECIFICATIONS, AND/OR (2) PROPERLY STORED, CURED, AND USED UNDER NORMAL OPERATING CONDITIONS. Carboline assumes no responsibility for coverage, performance, injuries, or damages resulting from use of the product. If this product is found not to perform as specified upon inspection by a Carboline representative during the warranty period, Carboline's sole obligation, if any, is to replace the Carboline product(s) proven to be defective or refund the purchase price thereof, at Carboline's sole option. Carboline shall not be liable for any other losses or damages. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated. The whole text of this Product Data Sheet, as well as the documents derived from it, have been written in English, and for legal purposes the English version shall prevail.