

The following Carboline products have been tested per ASTM E736 and determined acceptable as primers for Pyrocrete 241. Carboline Company does not claim repeatability of these tests as may be influenced by cure time, primer recoat characteristics, site conditions, or other factors beyond our control. Consult the individual Product Data Sheets for application and recoat instructions. Use of primers other than those listed below is not recommended without prior consultation and approval by the Carboline Fireproofing Technical Service Group.

Primer	Generic Type	VOC Content (g/l)
Galvanizing	-	-
Carbozinc 11	Solvent Based Inorganic Zinc	As supplied: EPA Method 24: 4.0 lbs./gal (479 g/l)
Carbozinc 11 VOC	Solvent Based Inorganic Zinc	As supplied: EPA Method 24: 3.20 lbs./gal (389 g/l)
Carbozinc 858 (3K)	Solvent Based Organic Zinc-Rich Epoxy	As supplied: 2.65 lbs./gal (318 g/l)
Carbozinc 859	Organic Zinc-Rich Epoxy	As supplied: 2.72 lbs./gal (326 g/l)
Carboguard 635	Epoxy Phenalkamine	As supplied: 2.47 lbs./gal (296 g/l mixed)
<i>Carboguard 880</i>	<i>Epoxy Polyamide</i>	<i>As supplied: 1.98 lbs./gal (238 g/l)</i>
Carboguard 890	Cycloaliphatic Amine Epoxy	As supplied: 1.81 lbs./gal (217 g/l)
Carboguard 893	Cycloaliphatic Amine Epoxy	As supplied: 1.6 lbs./gal (195 g/l)
Carboguard 893-SG	Epoxy polyamide with corrosion inhibitor (zinc phosphate)	As supplied: 2.70 lbs./gal (324 g/l)
Carbomastic 94	Polyamide Epoxy with corrosion inhibitor, (zinc phosphate)	As supplied: 1.0 lbs./gal (120 g/l)
Carbomastic 615	Phenalkamine epoxy	As supplied: 1.44 lbs./gal (172 g/l)
<i>Carboline 801</i>	<i>Two component, cross-linked epoxy</i>	<i>As supplied: 1.74 lbs./gal (208 g/l)</i>
Carbocoat 150 UP	Single Component Phenolic Modified Alkyd	As supplied: 3.4 lbs./gal (407 g/l)
Rustbond	Polymeric epoxy amine	As supplied: EPA Method 24 0.7 lbs./gal (85 g/l)